

CERTIFICATE

TÜV NORD CERT GmbH
herewith declares that

Mysolar Manufacturing (Shanghai) Co., Ltd.
Room J8097, Bldg 2, No. 4268, Zhennan Rd
Jiading District, Shanghai City, 201800
P.R. China

is authorized to provide the product mentioned below with the mark as illustrated:



Description of product (details see Annex 2):

Single glass PV Modules with 6" half-cut Mono-crystalline Silicon Solar Cells

Single glass PV Modules with 6" 1/6-cut Shingled Mono-crystalline Silicon Solar Cells

Double glass Bifacial PV Modules with 6" half-cut Mono-crystalline Silicon Solar Cells

Valid until: 2024-09-26

Tested according to: IEC 62716:2013 / EN 62716:2013 + AC:2014.
Registered No.: 44 780 20 406749 - 041
Manufacturer: see Annex 1
Test Report No.: 492011378.001
File No.: SHV02024/20-01



Essen, 2020-02-27



TÜV NORD CERT GmbH
Certification Body
Consumer Products

Please also pay attention to the information stated overleaf.

Anlage 1 zum Zertifikat Nr.: / Annex 1 to Certificate No.: 44 780 20 406749 - 041

Seite / Page 1 von / of 1

Aktenzeichen: / File reference: SHV02024/20-01

2020-02-27

Manufacturer:

Manufacturer: Coded by debtor no. 55450058

Factory inspection report no.: 862010455.001

Remark:

Factory inspection is mandatory to be performed annually. Please refer to factory inspection report for detailed information.

A handwritten signature in blue ink, appearing to read "Rohrleitungs".

TÜV NORD CERT GmbH
Certification Body
Consumer Products

Description of product(s):

| | |
|------------------------------|---|
| Module types: | Single glass PV Modules with 6" half-cut Mono-crystalline Silicon Solar Cells: 144 cells: MSxxxM-HS (xxx=380-405, in increments with 5) 120 cells: MSxxxM-HS (xxx=320-335, in increments with 5) |
| Maximum system voltage: | 1000V |
| Fuse rating: | 15A |
| Application class: | Class A |
| Electrical protection class: | Class II |
| Module types: | Single glass PV Modules with 6" 1/6-cut Shingled Mono-crystalline Silicon Solar Cells: 486 cells: MSxxxM-SLS (xxx=370-430, in increments with 5) 396 cells: MSxxxM-SLS (xxx=305-350, in increments with 5) |
| Maximum system voltage: | 1000V |
| Fuse rating: | 15A |
| Application class: | Class A |
| Electrical protection class: | Class II |
| Module types: | Double glass Bifacial PV Modules with 6" half-cut Mono-crystalline Silicon Solar Cells: 144 cells: MSxxxM-DHBS (Albedo: 0%, xxx=360-405, in increments with 5) (Albedo: 20%, xxx=420-465, in increments with 5) 120 cells: MSxxxM-DHBS (Albedo: 0%, xxx=300-335, in increments with 5) (Albedo: 20%, xxx=350-385, in increments with 5) Remark: When Albedo is 0% xxx indicate the front side output power. When Albedo is 20% xxx indicate the comprehensive output power of both sides. |
| Maximum system voltage: | 1500V |
| Fuse rating: | 20A |
| Application class: | Class A |
| Electrical protection class: | Class II |
| Remark: | For detailed product information, please refer to CDF (Constructional Data Form) in Annex 1 of test report. |



TÜV NORD CERT GmbH
Certification Body
Consumer Products